



Product Code	LAG-CHR-91423C
Description	In-wall Body of 3-Hole Basin Mixer
Flow Rate	93.28 LPM @ 3 bar
Recommended Water Pressure	0.5 Bar - 5 Bar
water Pressure	Brass Ingots as per IS:1264-1997
Brass Specification in Percentage	Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder)
	Brass Rod as per IS:319-1989
	Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)
Contridas	Fittings: Components have WRAS Approved for food grade conformity with Brass Housing and
Cartridge	Spindle
Specification	Life Cycle EN 200: 200,000 cycles (Standard) - 5.0 LAC Cycles as per EN 200*
Water Tightness	16 bar (Pass)
Pressure Resistance	25 bar (Pass)
Available Colour Finishing	CHROME (CHR)

^{*} As per in-house testing done on automatic life cycle testing machine made by Giussain, Italy

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. Jaquar reserves the right to make the necessary amendments at any time without prior notice.