



THERMOSTATIC SHOWER MIXER BODY

TOUCH CONTROL PANEL PLASTIC BOX

Product Code	QLD-CHR-309661C
Description	QLOUD Thermostatic Shower Mixer Body and Touch Control Panel Plastic box for In-wall installation
Flow Rate	53.00 LPM @ 3 bar
Recommended Water Pressure	1.0 Bar- 6.0 bar
Water Connections	Inlet and Outlet : 3/4" BSP/20mm
Material Specification in Percentage	<p>Brass Ingots as per IS:1264-1997 Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder)</p> <p>Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p>
Specification	<ul style="list-style-type: none"> • Cartridges made of high performance thermostatic polymer materials that meet the global standards for high and low pressure • High technology thermoplastic polymer minimises lime-scale build up • Standard temperature range: 15° C to 60° C (59-104° F) • Shower mixer contains ceramic cartridge for ON & OFF function. • Protected against backflow
Available Colour Finishing	CHROME (CHR)

* As per in-house testing done on automatic life cycle testing machine made by Giussani, Italy

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.