



BATH + LIGHT

BOLLARD 8W

Visio LED Bollard

Outdoor Luminaire

Product Code:

LBLD06R108XW

8W - 800lm - 3000K - CRI>70 Ra - Beam Angle - Asymmetric



Technical Specifications

Operating Temperature	-10°C to 50°C
Rated Input Voltage & Frequency	220-240 V AC, 50 Hz
Rated Input Wattage	8W ± 10%
Rated Input Current	0.040 Amp (Nominal)
Power Factor	>0.90
ATHD	<20%
Rated Luminous Flux	800 lm (tolerance as per BIS)
Rated Luminaire Efficacy	100 lm/W (tolerance as per BIS)
Correlated Color Temperature (CCT)	3000 K (tolerance as per ANSI)
Color Rendering Index (CRI)	>70 Ra
Beam Angle	Asymmetric
Driver Efficiency	≥80%
LED Life Span	>50000 Hrs (Ta=25°C @L70)
Housing	Aluminium Die Cast with Powder Coating
Lens / Reflector	Tempered Glass Diffuser
Mounting	Surface

Protections

Over Voltage Protection	300 V AC upto 20 min.
Surge Protection	±2.0KV
Protection Class	Class I
Ingress Protection (IP Rating)	IP54
Short Circuit Protection	Provided
Open Circuit Protection (No Load)	Provided
Reverse Polarity Protection	Provided

All technical data is subject to industry-standard tolerances.

Product Dimensions (Dia. x H)

Ø145 X 600 mm (tol.±5 mm)



Applications

Residences, Offices, Small Retail Shops, Hotels, Coffee Shops, Restaurants, Hospitals, area lighting and for other outdoor applications.