jaquar.com	
Document No.	
SNW/SLS/24/953BIUFSM	
520 75 445 68 016 360 TOP VIEW	SIDE VIEW
General Information	
Product Code	SLS-WHT-6953BIUFSM
Brand	Jaquar
Colour	White
Туре	Wall Hung WC
Material	Ceramic-Vitreous China (VC)
Product Specification	
Product Dimension	375x520x400 mm
Bowl Opening (Inner Dimension)	280x360 mm
Product Net Weight	23.5 kg.
Product Gross Weight	29.5 kg.
Packaging Dimension	460x410x550 mm
Outlet	Horizontal
	Internal diameter of inlet hole dia. Ø 58 \pm 3 mm
Inlet And Outlet Hole Dimension	External diameter of outlet hole dia. Ø 100 \pm 5 mm
Product Features	
White Finish, Blind Installation Rimless Bowl Design, Detachable Slim Seat Cover, Trap glaze, Dual Flush-2.8/4.8 LPF Anti germ glaze, Trapwash	 (L) From wall tile surface to center of seat cover fixing hole (La) WC Fixing wall thickness (Lb) From wall tile surface to the inner bowl surface of WC
ACCESSORIES PROVIDED	
Seat Cover	SLS-WHT-6103UF
Inlet outlet Gasket	ZPS-WHT-GK01
Fixing kit ACCESSORIES RECOMMENDATION	ZPS-WHT-FB13
ACCESSORIES RECOMMENDATION Rack bolt	ZPS-SNS-RB07N
Concealed cistern	JCS-WHT-24005, 2400P, 2400, 2400WS, 2400WP, 2400FS, 2400FP, 2431P, 2431FP, 2431, 2431S, 2431FS
CARE AND CLEANING GUIDELINES	
\neg Vitreous china sanitary ware products are fragile in nature and ne thereafter.	eed to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use
thereafter.	
thereafter. — The product is heavy and it is recommended that two persons hol	old it while it is being fixed.
thereafter. The product is heavy and it is recommended that two persons hold Carefully inspect the new product for damage before installation.	old it while it is being fixed.
thereafter. — The product is heavy and it is recommended that two persons hol — Carefully inspect the new product for damage before installation. — Risk of product damage. Over tightening may cause breakage or c	old it while it is being fixed. chipping of vitreous china.
thereafter. — The product is heavy and it is recommended that two persons hol — Carefully inspect the new product for damage before installation. — Risk of product damage. Over tightening may cause breakage or c — Risk of external leakage. Do not lift or rock the bowl after placement	old it while it is being fixed. chipping of vitreous china. ment.
thereafter. The product is heavy and it is recommended that two persons hol Carefully inspect the new product for damage before installation. Risk of product damage. Over tightening may cause breakage or c Risk of external leakage. Do not lift or rock the bowl after placeme Always test your cleaning solution on an inconspicuous area on th	old it while it is being fixed. chipping of vitreous china. ment.
thereafter. — The product is heavy and it is recommended that two persons hol — Carefully inspect the new product for damage before installation. — Risk of product damage. Over tightening may cause breakage or c — Risk of external leakage. Do not lift or rock the bowl after placeme — Always test your cleaning solution on an inconspicuous area on th — Do not allow cleaners to sit or soak on the product.	old it while it is being fixed. chipping of vitreous china. lent. he product before applying it to the entire surface.
thereafter. — The product is heavy and it is recommended that two persons hol — Carefully inspect the new product for damage before installation. — Risk of product damage. Over tightening may cause breakage or c — Risk of external leakage. Do not lift or rock the bowl after placeme — Always test your cleaning solution on an inconspicuous area on th — Do not allow cleaners to sit or soak on the product. — Use a soft, dampened sponge or cloth to clean. Never use abrasiv	old it while it is being fixed. .
thereafter. ¬ The product is heavy and it is recommended that two persons hol ¬ Carefully inspect the new product for damage before installation. ¬ Risk of product damage. Over tightening may cause breakage or c ¬ Risk of external leakage. Do not lift or rock the bowl after placeme ¬ Always test your cleaning solution on an inconspicuous area on th ¬ Do not allow cleaners to sit or soak on the product. ¬ Use a soft, dampened sponge or cloth to clean. Never use abrasiv ¬ Wipe surfaces clean and rinse completely with water immediately	old it while it is being fixed. .
thereafter. — The product is heavy and it is recommended that two persons hol — Carefully inspect the new product for damage before installation. — Risk of product damage. Over tightening may cause breakage or c — Risk of external leakage. Do not lift or rock the bowl after placeme — Always test your cleaning solution on an inconspicuous area on th — Do not allow cleaners to sit or soak on the product. — Use a soft, dampened sponge or cloth to clean. Never use abrasiv — Wipe surfaces clean and rinse completely with water immediately	old it while it is being fixed. chipping of vitreous china. ment. he product before applying it to the entire surface. we material like a bristle brush or scouring pad. y after applying cleaners. leaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
thereafter. The product is heavy and it is recommended that two persons hol Carefully inspect the new product for damage before installation. Risk of product damage. Over tightening may cause breakage or c Risk of external leakage. Do not lift or rock the bowl after placeme Always test your cleaning solution on an inconspicuous area on th Do not allow cleaners to sit or soak on the product. Use a soft, dampened sponge or cloth to clean. Never use abrasiv Wipe surfaces clean and rinse completely with water immediately Clean Chrome, stainless steel surfaces once a week. Do not use cl	old it while it is being fixed. chipping of vitreous china. ment. he product before applying it to the entire surface. we material like a bristle brush or scouring pad. y after applying cleaners. leaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.