




General Information

Product Code	ZPS-WHT-VB01
Brand	Jaquar
Colour	White
Type	P-trap to S-trap Conversion Bend
Material	ABS(Acrylonitrile Butadiene Styrene) Plastic

Product Specification

Product Dimension	300x140x145mm
Product Net Weight	570 Gram
Product Gross Weight	740 gram
Trap distance	Adjustable: 90 to 195mm with plate & 100 to 200mm without plat
Inlet And Outlet Hole Dimension	Inlet diameter : PP Outer 145 , PP Inner 115 and with rubber outer 145 and rubber inner 85 mm
	Outlet diameter : PVC Outer 90 , PVC Inner 85 and with rubber outer 115 and rubber inner 90 mm
Product Feature	Conversion bends can be used to connect solvent weld waste pipes and fittings to push-fit waste pipes and fittings, and vice versa.

ACCESSORIES PROVIDED

PP & Rubber Upper Gasket	
Rubber Lower Gasket	
Fixing kit	1 Long Threaded Rod, 1 Fixing Plate, 4 Screw, 4 Sleeve, 2 Washers, 2 Nut. 

CARE AND CLEANING GUIDELINES

- Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- The product is heavy and it is recommended that two persons hold it while it is being fixed.
- Carefully inspect the new product for damage before installation.
- Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- Risk of external leakage. Do not lift or rock the bowl after placement.
- Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- Do not allow cleaners to sit or soak on the product.
- Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

QUALITY MANAGEMENT SYSTEM - ISO 9001



DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice.

For Installation Refer Actual Product