

### **KUBS 8W**


Kubs LED Up & Down Wall Light

**Outdoor Luminaire**

**Product Code:**

404LS4X2H.NHG

8W - 560lm - 3000K - CRI>70 Ra - Beam Angle - 10°



### **Technical Specifications**

Operating Temperature	-10°C to 40°C
Rated Input Voltage & Frequency	220-240 VAC, 50Hz
Rated Input Wattage	8W ± 10%
Rated Input Current	0.070 Amp (Nominal)
Power Factor	≥0.50
ATHD	<20%
Rated Luminous Flux	560 lm (tolerance as per BIS)
Rated Luminaire Efficacy	70 lm/W (tolerance as per BIS)
Correlated Color Temperature (CCT)	3000 K (tolerance as per ANSI)
Color Rendering Index (CRI)	>70 Ra
Beam Angle	10°
Driver Efficiency	≥80%
LED Life Span	>50000 Hrs (Ta=25°C @L70)
Housing	Aluminium Die Cast with Grey Powder Coating
Lens / Reflector	Transparent Polycarbonate Diffuser



### **Protections**

Over Voltage Protection	Withstand upto 300V/AC for 4 Hrs.
Surge Protection	±2.0KV
Protection Class	Class II
Ingress Protection (IP Rating)	IP65
Impact Protection (IK Rating)	IK07
Short Circuit Protection	Provided
Open Circuit Protection (No Load)	Provided
Reverse Polarity Protection	Provided

All technical data is subject to industry-standard tolerances.

## Product Dimensions (L x W x H)

124 X 90 X 124 mm (tol.±5 mm)



## Applications

Applications Residences, Offices, Small Retail Shops, Hotels, Coffee Shops, Restaurants, Hospitals, area lighting and for other indoor applications.