

### LYRAS 5W


Up Lyras 130 LED Wall Light

**Outdoor Luminaire**

**Product Code:**

465LL5X1H.NHG

5W - 350lm - 3000K - CRI>70 Ra - Beam Angle - 40°



### Technical Specifications

Operating Temperature	-10°C to 40°C
Rated Input Voltage & Frequency	220-240 VAC, 50Hz
Rated Input Wattage	5W ± 10%
Rated Input Current	0.025 Amp (Nominal)
Power Factor	≥0.9
Rated Luminous Flux	350 lm (tolerance as per BIS)
Rated Luminaire Efficacy	70 lm/W (tolerance as per BIS)
Correlated Color Temperature (CCT)	3000 K (tolerance as per ANSI)
Color Rendering Index (CRI)	>70 Ra
Beam Angle	40° (within the permissible limits)
Driver Efficiency	≥75%
LED Life Span	>50000 Hrs (Ta=25°C @L70)
Housing	Die Cast Aluminium with Powder Coating
Lens / Reflector	Transparent Glass Diffuser
Mounting	Wall



### Protections

Over Voltage Protection	Withstand upto 300V/AC for 4 Hrs.
Surge Protection	±2.0KV
Ingress Protection (IP Rating)	IP66
Impact Protection (IK Rating)	IK08
Short Circuit Protection	Provided
Open Circuit Protection (No Load)	Provided
Reverse Polarity Protection	Provided

All technical data is subject to industry-standard tolerances.

## Product Dimensions (L x W x H)

Ø86 X 138 X 174 mm (Tol.±5 mm)



## Applications

Applications Residences, Offices, Small Retail Shops, Hotels, Coffee Shops, Restaurants, Hospitals, area lighting and for other indoor applications.