



<b>Product Code</b>	HSH-CHR-1729
<b>Description</b>	Multifunction 140mm Round Shape Hand Shower with Rain & Massage Spray with Air Effect
<b>Flow Rate</b>	“Normal - 13.06 LPM @ 3 bar Massage - 12.98 LPM @ 3 bar”
<b>Flow regulator</b>	By using flow regulators + Brass Housing (Product should be ordered with suffix as GA-6.0 LPM, GB-8.0 LPM, & GC-12.0 LPM @ 3.0 Bar pressure) one can regulate the flow rate.
<b>Recommended Water Pressure</b>	1.0 Bar - 3.0 Bar
<b>Spray Modes</b>	Normal (rain) and Booster massage functions
<b>ABS Specification in Percentage</b>	Specific Gravity g/cm <sup>2</sup> (1.06-1.10), Melt Mass Flow Rate g/10 min. (20-26), Rockwell Hardness (95-115), DTUL @ 66 psi /0.45 MPa 0C (78-102)
<b>Technology</b>	<p><b>“Unique Air Technology</b> - Air is mixed in the water through a built-in air mixer which is a part of the shower. This leads to lighter voluminous drops which reduce water consumption by 30% and also assuring a soft and refreshing shower</p> <p><b>Advanced Rubit</b> - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel.</p> <p><b>Click Position System</b> - One can feel and hear the click while changing the function of the shower sprays.</p> <p><b>Booster Technology</b> - Creates the sensation of a full shower regardless of the water pressure</p> <p><b>Thermo Insulation</b> - Insulated shower systems prevent scalding and don't heat up the shower body.”</p>
<b>Finish</b>	“Salt Spray (350 hrs + Validated) Adhesion (Pass)”
<b>Available Finishing</b>	CHROME (CHR)
<p>DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.</p>	