



| | |
|---|--|
| Product Code | OHS-CHR-1999 |
| Description | Multifunction 100mm Round Shape Overhead Shower with Rain, Soft & Massage Spray |
| Flow Rate | “Normal - 14.59 LPM @ 3 bar Soft - 13.09 LPM @ 3 bar Massage - 10.11 LPM @ 3 bar” |
| Flow regulator | By using flow regulators + Brass Housing (Product should be ordered with suffix as GA-6.0 LPM, GB-8.0 LPM, & GC-12.0 LPM @ 3.0 Bar pressure) one can regulate the flow rate. |
| Recommended Water Pressure | 1.0 Bar - 3.0 Bar |
| Mount Type | Wall Mounting |
| Spray Modes | Normal, Soft and Massage functions |
| Material Composition Specification in Percentage | <p>“Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> <p>ABS Specification Specific Gravity g/cm² (1.06-1.10), Melt Mass Flow Rate g/10 min. (20-26), Rockwell Hardness (95-115), DTUL @ 66 psi /0.45 MPa OC (78-102)”</p> |
| Technology | <p>“Advanced Rubit - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel.</p> <p>Click Position System - One can feel and hear the click while changing the function of the shower sprays.”</p> |
| Finish | “Salt Spray (350 hrs + Validated) Adhesion (Pass)” |
| Available Finishing | CHROME (CHR) |
| DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice. | |