



Product Code	ALD-CHR-681NE
Description	Aquamax In-wall Body of Thermostatic Shower Mixer with Fixing Lugs & 2-way diverter (Without Exposed Parts)
Flow Rate	42.00 LPM @ 3 bar
Recommended Water Pressure	0.2 Bar- 5 bar
Brass Specification in Percentage	Brass Ingots as per IS:1264-1997 Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder) Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)
Specification	<ul style="list-style-type: none">• Cartridges made of high performance thermostatic polymer materials that meet the global standards for high and low pressure• High technology thermoplastic polymer minimises lime-scale build up• Standard temperature range: 15° C to 60° C (59-104°F)• Shower mixer contains ceramic cartridge for divert water in two outlets.• Protected against backflow
Water Tightness	16 bar (Pass)
Pressure Resistance	25 bar (Pass)
Available Colour Finishing	CHROME (CHR)
* As per in-house testing done on automatic life cycle testing machine made by Giussani, Italy	
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.	