



|   |  |
|---|--|
| <b>Product Code</b>   | HSB-CHR-49537  |
| <b>Description</b>  | Single Function 25X38mm Oval Shape Hand Shower   |
| <b>Flow Rate</b>  | 25.65 LPM @ 3 bar  |
| <b>Flow regulator</b>   | By using flow regulators + Brass Housing (Product should be ordered with suffix as GA-6.0 LPM, GB-8.0 LPM, & GC-12.0 LPM @ 4.0 Bar pressure) one can regulate the flow rate. |
| <b>Recommended Water Pressure</b>   | 1.0 Bar - 3.0 Bar  |
| <b>Spray Modes</b>  | Single Function  |
| <b>ABS Specification in Percentage</b>  | Specific Gravity g/cm <sup>2</sup> (1.06-1.10), Melt Mass Flow Rate g/10 min. (20-26), Rockwell Hardness (95-115), DTUL @ 66 psi /0.45 MPa 0C (78-102)                       |
| <b>Technology</b>   | <b>Advanced Rubit</b> - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel.  |
| <b>Finish</b>   | Salt Spray (350 hrs + Validated)<br>Adhesion (Pass)  |
| <b>Available Finishing</b>  | CHROME (CHR)   |
| DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice. |  |