





Product Code	OHS-CHR-1679
	Maze Prime Square Shape Single Function Shower 450 X 450mm AISI 304 stainless steel in chrome finish with
	RGB LED light remote control & installation kit for false ceiling
Description	• Chromo therapy (RGB): LED x 0.23W with 12V Power Supply (SMPS) Including Controller, connecting to AC
	100-240V, 50-60Hz
Flow Rate	47.00 LPM @ 3 bar
Flow regulator	By using flow regulators + Brass Housing (Product should be ordered with suffix as GA-6.0 LPM, GB-8.0 LPM & GC-12.0 LPM @ 4.0 Bar pressure) one can regulate the flow rate.
Recommended Water Pressure	1.0 Bar - 3.0 Bar
Mount Type	Ceiling Mounting
Spray Modes	Single Function
Material Composition Specification in Percentage	STAINLESS STEEL: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304) ABS: Specific Gravity (g/cm²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTUL @ 66 psi (0.45 MPa) (0C) 78-102
REMOTE CONTROL	Automatic mode changing - next Speed Down Push - button to speed down percrame mode Mono color - next Mono color - previous Mono color - previous Automatic mode changing - next Speed Up Push - button to speed down pencramic mode Increase Brightness of LED Decrease Brightness of LED Automatic mode changing previous HOW TO CHANGE BATTERY
LED POWER SUPPLY	CHROMO THERAPY (RGB) LED x 0.23W with 12V Power Supply (SMPS) including Controller, connecting to AC 100-240V, 50-60Hz COLOR VARIATION • Mono Color (RGB) Chromo Theraphy LED On / Off Switch Sensor by Remote Control
Technology	Advanced Rubit - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel.
Registered design no.	276017
Finish	Salt Spray (350 hrs + Validated) Adhesion (Pass)
Available Finishing	Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Black Matt (BLM), Graphite (GRF) & Stainless Steel Finish (SSF)
DISCLAIMER: Our every effort has	s been made to ensure factual accuracy, the information presented subject to changes due to requirements in
different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary	

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.