



| | |
|---|---|
| Product Code | ALD-CHR-683N |
| Description | Aquamax In-wall Body of Thermostatic Shower Mixer with 3-way diverter (Without Exposed Parts) |
| Flow Rate | 52.00 LPM @ 3 bar |
| Recommended Water Pressure | 0.2 Bar- 5 bar |
| Brass Specification in Percentage | <p>Brass Ingots as per IS:1264-1997 Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder)</p> <p>Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> |
| Specification | <ul style="list-style-type: none"> • Cartridges made of high performance thermostatic polymer materials that meet the global standards for high and low pressure • High technology thermoplastic polymer minimises lime-scale build up • Standard temperature range: 15° C to 60° C (59-104°F) • Shower mixer contains ceramic cartridge for divert water in three outlets. • Protected against backflow |
| Water Tightness | 16 bar (Pass) |
| Pressure Resistance | 25 bar (Pass) |
| Available Colour Finishing | CHROME (CHR) |
| * As per in-house testing done on automatic life cycle testing machine made by Giussani, Italy | |
| DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice. | |