



Product Code	OHS-CHR-1689
Description	Duoflo Shower Round Shape 250mm AISI 304 stainless steel with Installation kit for false ceiling <ul style="list-style-type: none"> • 2-functions <ul style="list-style-type: none"> ▪ Rain, ▪ Laminar
Flow Rate	Rain - 65.52 LPM @ 3 bar Laminar - 67.44 LPM @ 3 bar
Flow regulator	By using flow regulators + Brass Housing (Product should be ordered with suffix as GA-6.0 LPM, GB-8.0 LPM, & GC-12.0 LPM @ 4.0 Bar pressure) one can regulate the flow rate.
Recommended Water Pressure	1.0 Bar - 3.0 Bar
Mount Type	Ceiling Mounting
Spray Modes	Rain & Laminar Functions
Material Composition Specification in Percentage	STAINLESS STEEL: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304) ABS: Specific Gravity (g/cm ²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTUL @ 66 psi (0.45 MPa) (OC) 78-102
Technology	Advanced Rubit - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel.
Finish	Salt Spray (350 hrs + Validated) Adhesion (Pass)
Available Finishing	Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Blush Gold Bright PVD (BGP), Black Matt (BLM), Gold Bright PVD (GBP), Gold Matt PVD (GMP), Graphite (GRF) & Stainless Steel (SSF)

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.