



| | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Code | FUS-CHR-29173B |
| Description | Single Lever Mono Sink Mixer with Swivel Spout & 375mm Long Braided Hoses |
| Connection Size | Braided hoses, 1/2" FIP (WRAS Approved) Withstand pressure of 10 Bar |
| Flow Rate | 14.45 LPM @ 3 bar |
| Flow regulator | By using flow regulators (Product should be ordered with suffix as G-2.5 LPM, GA-6.0 LPM, GB-8.0 LPM, GC-13.0 LPM, GD-3.8 LPM & GE-1.3 LPM @ 3.0 Bar pressure) one can regulate the flow rate. |
| Recommended Water Pressure | 0.5 Bar - 5 Bar |
| Brass Specification in Percentage | <p>Brass Ingots as per IS:1264-1997 Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder)</p> <p>Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> <p>Brass Pipe as per IS:407-1996 Cu (62.0-65.0), Pb (0.0-0.3), Fe (0.0-0.01), Total Impurity (0.0-0.6), Zn (Remainder)</p> |
| Cartridge Specification | NSF-61 Approved Cartridge with Temperature Limiter Cartridge with Brass Spindle Life Cycle EN 817: 70,000 cycles (Standard) - 0.21 Million Cycles as per EN 817* - 1.05 Million Cycles (ON/OFF)* |
| Water Tightness | 16 bar (Pass) |
| Pressure Resistance | 25 bar (Pass) |
| Finish | Plating: Nickel-10.0 micron Chromium-0.3 micron Salt Spray (500 hrs + Validated) Adhesion (Pass) |
| Aerator Size | WRAS, ACS Approved (24X1) |
| Available Colour Finishing | CHROME (CHR) |
| * As per in-house testing done on automatic life cycle testing machine made by Giussain, Italy | |
| DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice. | |